



Burnishing & Refinishing



The Hawk High Speed is known for its balance, durability and value. HawkK offers the largest selection of burnishers in four sizes; 13", 15", 17" and 20" and three speeds; 1500, 1800 and 2000 RPM.

The 17" and 20" Active Dust Control DC models include a dust ring and filter, the perfect addition to any Green Cleaning program.

Power

- 1.5 HP, 66 frame, DC rectified motor. 115V, 50/60 Hz power. 230V optional.
- 50 ft. 14-3 STO industrial power cord with molded plug
- Multi V-Belt drives pads at 1500, 1800 and 2000 RPM

Engineering Design

- Welded steel frame. One piece chromed heavy duty steel handle with variable position positive lock.
- 13", 15", 17" and 20" steel brush covers with full wraparound bumper
- 17" and 20" Dust Control models include a dust ring and filter
- Thumb operated safety switch
- Negative pressure on/off switch
- Dual steel operating triggers
- Comfortable vinyl-dipped foam grip handle.
- 1" x 5" non-marking ball-bearing wheels
- Includes flexible pad holder with pad centering clamp

Safety Features

- Quiet operation - 69 dB (Standard), 62 dB (Dust Control). Meets GS42 standard.
- UL/CUL listed (1500 rpm model)
- Built with UL listed components



Specifications

Machine Pad Size	13" Standard 13"	15" Standard 15"	17" Standard 17"	17" Dust Control 16"	20" Standard 20"	20" Dust Control 19"
Speed	1500 RPM					
Model #	HP1513-HSB	HP1515-HSB	HP1517-HSB	HP1517-1500HSBDC	HP1520-HSB	HP1520-1500HSBDC
Part #	F1500-13	F1500-15	F1500-17	F1500-17DC	F1500-20	F1500-20DC
Amp Draw	9.1 Amp	9.6 Amp	13.0 Amp	12.2 Amp	13.8 Amp	13.1 Amp
Speed	1800 RPM					
Model #	HP1513-1800	HP1515-1800	HP1517-1800	HP1517-1800DC	HP1520-1800	HP1520-1800DC
Part #	F1800-13	F1800-15	F1800-17	F1800-17DC	F1800-20	F1800-20DC
Amp Draw	9.5 Amp	9.9 Amp	13.9 Amp	13.2 Amp	14.6 Amp	13.6 Amp
Speed	2000 RPM					
Model #	HP1513-2000	HP1515-2000	HP1517-2000	HP1517-2000DC	HP1520-2000	HP1520-2000DC
Part #	F2000-13	F2000-15	F2000-17	F2000-17DC	F2000-20	F2000-20DC
Amp Draw	10.0 Amp	10.8 Amp	14.9 Amp	13.9 Amp	16.4 Amp	14.8 Amp

All Models

Motor	1.5 HP, 66 frame DC rectified motor					
Power	115V, 50/60 Hz power. 50 ft. 14-3 STO industrial power cord with molded plug. (230V Optional)					
Belt Drive	Multi-V belt drive					
dB Rating	69 dB	69 dB	69 dB	62 dB	69 dB	62 dB
Machine Weight (all)	84 lbs.	86 lbs.	88 lbs.	90 lbs.	90 lbs.	92 lbs.

Subject to Change Without Notice